MS12/MS13 – 21 sqm

MOBILE LED SCREEN

All our Mobile LED Screens are built and approved according to TÜV regulations. They have all required construction books/"Baubücher" and are approved to be used up to wind speeds of 20 m/s or 72 km/h. All screens have multiple safety lock systems for the hydraulic system and are equipped with dual video processors linked in a redundant system. Please contact us for further information about Digital Banners, Info Channels etc.

TECHNICAL SPECIFICATIONS

Container screen
Display size: 21 m^2
Display dimensions: W: 6000 H:3500 mm
Display resolution: W: 1536 H: 896 px
Picture format: 16:9
Pixel pitch: 3,9 mm
Brightness: 5000 nits
Viewing angle: H: 120° V: 75°
Screen rotation: 360°
Min. rotation space from trailer body (each side): 1400 mm
Input signals: CVBS, SDI, HDSDI, DVI
Trim height: 2487 - 4135 mm
Built in studio: No
Built in generator: Yes, 18 kVA
Running time generator: 11 h
External power connector: 32 A, 3 phase, 400V, CEE
Power consumption (max): 29 A
Container on ground dimensions: L: 5000 W: 2550 H: 2440 mm
Ground space outriggers when rigged: L: 5000 W: 3000 mm
Weight, container on ground: 5500 kg
Trailer
Trailer dimensions with one container: L: 7000 W: 2550 H: 3440 mm
Weight, container on trailer: 9600 kg
Truck (front & back, tool required)
Truck dimensions with one container: L: 7500 W: 2550 H: 3440 mm
Length, total (truck & trailer): 14300 mm
Weight, total (truck, trailers with containers): 22300 kg
Weight, truck with container: 13200 kg